



Bestellservice
Order service

<http://shop.rc-electronic.com>
shop@rc-electronic.de
+49 (0) 8234 / 95 98 90

LED-Nachbrennerringe

LED after burner rings

Produktbeschreibung und Features

LED-Ringe zur Simulation von Nachbrennern in fünf verschiedenen Größen. Die Nachbrennerringe können z. B. mit der Optotronix Aurora LCU (Artikel-Nr. OPT2000, Seite 8) oder der Optotronix SkyFire LCU (Artikel-Nr. OPT2050, Seite 12) angesteuert werden.

Montage- und Einbauhinweis

Zur Montage der LED-Nachbrennerringe sind Lötarbeiten notwendig. Bei der Installation muss der entsprechende Vorwiderstand in die Plus- oder Minusleitung eingelötet werden.

Lieferumfang

1 LED-Nachbrennerring inkl. 1,5m Silikonzuleitungskabel.

Product description and features

LED rings for simulating afterburners in five different sizes. The afterburner rings can be controlled with Optotronix Aurora LCU (item no. OPT2000, page 8) or Optotronix SkyFire LCU (item no. OPT2050, page 12).

Mounting and assembly notice

For mounting the LED afterburner rings soldering work is necessary. When installing the included pre-resistor must be soldered into the plus or minus pole.

Delivery contents

1 LED after burner ring with 1.5m (59.06in) silicon cable.



Kompatible Artikel
Compatible items

Lichtsteuermodul FireFly LCU EVO2
Light control unit FireFly LCU EVO2
Seite 6 Page 6






Lichtsteuermodul Aurora LCU EVO2
Light control unit Aurora LCU EVO2
Seite 8 Page 8

Lichtsteuermodul SkyFire LCU
Light control unit SkyFire LCU
Seite 12 Page 12

Widerstände 3W
Resistors 3W
Seite 54 Page 54



Bestellinformation <i>Order information</i>	
Bezeichnung <i>Description</i>	Art.-Nr. <i>Item no.</i>
LED-Nachbrennerring, 45mm <i>LED afterburner ring, 45mm (1.77in)</i>	OPT4160
52,95 EUR inkl. MwSt. <i>incl. VAT</i>	
LED-Nachbrennerring, 80mm <i>LED afterburner ring, 80mm (3.15in)</i>	OPT4165
85,95 EUR inkl. MwSt. <i>incl. VAT</i>	
LED-Nachbrennerring, 100mm <i>LED afterburner ring, 100mm (3.94in)</i>	OPT4170
100,95 EUR inkl. MwSt. <i>incl. VAT</i>	
LED-Nachbrennerring, 120mm <i>LED afterburner ring, 120mm (4.72in)</i>	OPT4175
112,95 EUR inkl. MwSt. <i>incl. VAT</i>	
LED-Nachbrennerring, 160mm <i>LED afterburner ring, 160mm (6.30in)</i>	OPT4180
192,95 EUR inkl. MwSt. <i>incl. VAT</i>	



Widerstände <i>Resistors</i>					
Akkutyp <i>Battery type</i>	45mm <i>1.77in</i>	80mm <i>3.15in</i>	100mm <i>3.94in</i>	120mm <i>4.72in</i>	160mm <i>6.30in</i>
NiMH	0R68	0R47	0R33	0R33	0R33
2S LiPo/Lilon	2R7	1R8	1R5	1R2	0R5**
2S LiFePO4	1R	0R56	0R47	0R33	0R33

Technische Daten <i>Specifications</i>					
	45mm <i>1.77in</i>	80mm <i>3.15in</i>	100mm <i>3.94in</i>	120mm <i>4.72in</i>	160mm <i>6.30in</i>
Anzahl LEDs <i># of LEDs</i>	36	60	75	87	210
max. Strom <i>max. current</i>	0,8A <i>0.8A</i>	1,4A <i>1.4A</i>	1,75A <i>1.75A</i>	2,00A <i>2.00A</i>	4,90A <i>4.90A</i>
Spannung <i>Voltage</i>	6,6V <i>6.6V</i>	6,6V <i>6.6V</i>	6,6V <i>6.6V</i>	6,6V <i>6.6V</i>	6,6V <i>6.6V</i>
Gewicht <i>Weight</i>	25g <i>0.8oz</i>	27g <i>0.87oz</i>	30g <i>0.96oz</i>	31,5g <i>1.01oz</i>	46,5g <i>1.5oz</i>